



# FILTER

Model: 201 K2P3 R D  
P/N 124320000

Combined filter with standard thread connector to **EN 148-1** for Ammonia (NH<sub>3</sub>) and its derivatives, dusts, fumes, mists.

The filter can be used with full face masks type **TR 82**, **TR 2002 CL2** and **TR 2002 CL3**, halfmasks **ST 85** or equivalent, provided that they are fitted with EN 148-1 connector.



## TECHNICAL DATA

### Inhalation resistance

at 30 l/min: 1.2 mbar  
at 95 l/min: 4.4 mbar

### Duration at gases

Filter type	Class	Testing Gas	Testing Concentration (PPM)	Testing Flow (l/min)	Testing HR (%)	Breakthrough concentration (PPM)	Duration Required (min)	Duration Tested (min)
K	2	NH <sub>3</sub>	5000	30	70	25	40	55

### Performance particle filtration

Filter type	Penetration (l/min)	Testing Aerosol	Penetration Max Allowed (%)	Test 1 (%)	Test 2 (%)	Test 3 (%)
P R	95	NaCl	0.05	0.0019	0.0019	0.0008
		Paraffin oil	0.05	0.0007	0.0008	0.0009

Test Filter Type - Performance Particle Filtration to register:

Test 1: Penetration (media calculated 30 sec after the test beginning)

Test 2: Max Penetration till 120 mg aerosol exposition

Test 3: Penetration (media calculated 30 sec after the test beginning) after 120 mg aerosol exposition and 24h storage

Marking R means that the filter is reusable for more than one workshift.

# FILTER

Model: 201 K2P3 R D

P/N 124320000

## "D" clogging test with Dolomite Dust.

Filter is submitted to an obstruction test with a concentration of Dolomite of 263 mg.h.m<sup>3</sup>.

Inhalation resistance: a 95 l/min: 8.4 mbar (request < 10.5 bar)

Filter type	Testing Flow	Testing Aerosol	Penetration Max Allowed (%)	Penetration Max Measured (%)
P R	95	NaCl	0.05	0.0008
		Paraffin oil	0.05	0.0008

Marking D means the filter passed the clogging test with Dolomite dust and it has high performance in dusty and sandy settings.

## Limitations for use

Do not use in areas where the oxygen concentration is lower than 17% in volume nor in presence of gases different from those clearly indicated.

## CLASSIFICATION

Filter complying with Directive **89/686/EEC (PPE)**

**Combined Filter, class 2** for gas protection and particle filter **class P3 R**, to **EN 14387:2004 + A1:2008**.

Label colour code: green, white.

## MARKING



## MATERIALS

Housing: polypropylene

Filter Media: activated carbon and filter paper

## STORAGE

Store at temperatures between -20 and +50 °C and RH <80%

## WEIGHT

210 g approximately

## DIMENSIONS/PACKING

The filter is sold in 4 piece boxes with dimensions 220 x 220 x 90 mm

## SHELF LIFE

Filters duly stored and in their original packaging will last five years from production. The expiry date is stamped onto the filter label and its packaging.

For more information please check the notes along with the products or the ones published on the website: [www.spasciani.com](http://www.spasciani.com)

NOTE: SPASCIANI SpA does not take any responsibility for any possible and unintentional mistake and reserve the faculty of modify materials and technical characteristics of its products at any time and without any notice. The pictures are purely indicative and may not represent the actual product described in the text.