



FILTER

Model: 203 A2B2E2K2HgP3 R D
P/N 124540000

Combined filter with standard thread connector to **EN 148-1** for organic vapours having boiling point higher than 65°C, inorganic gases and vapours, Sulphur Dioxide (SO₂), Ammonia (NH₃) and its derivatives, dusts, fumes and mists.

The filter can be used with full face masks type **TR 82**, **TR 2002 CL2** and **TR 2002 CL3** or equivalent, provided that they are fitted with EN 148-1 connector



TECHNICAL DATA

Inhalation resistance
 at 30 l/min: 1.9 mbar
 at 95 l/min: 6.9 mbar

Duration at gases

| Filter type | Class | Testing Gas | Testing Concentration (PPM) | Testing Flow (l/min) | Testing HR (%) | Breakthrough concentration (PPM) | Duration Required (min) | Duration Tested (min) |
|-------------|-------|--------------------------------|-----------------------------|----------------------|----------------|----------------------------------|-------------------------|-----------------------|
| A | 2 | C ₆ H ₁₂ | 5000 | 30 | 70 | 10 | 35 | 48 |
| B | 2 | Cl ₂ | 5000 | 30 | 70 | 0.5 | 20 | 32 |
| | | H ₂ S | 5000 | 30 | 70 | 10 | 40 | 46 |
| | | HCN | 5000 | 30 | 70 | 10 | 25 | >35 |
| E | 2 | SO ₂ | 5000 | 30 | 70 | 5 | 20 | 28 |
| K | 2 | NH ₃ | 5000 | 30 | 70 | 25 | 40 | 52 |
| Hg | / | Hg | 1000 | 30 | 70 | 10 | 100 | >120 |

Performance particle filtration

| Filter type | Penetration (l/min) | Testing Aerosol | Penetration Max Allowed (%) | Test 1 (%) | Test 2 | Test 3 |
|-------------|---------------------|-----------------|-----------------------------|------------|--------|--------|
| P R | 95 | NaCl | 0.05 | 0.0019 | 0.0019 | 0.0008 |
| | | Paraffin oil | 0.05 | 0.0007 | 0.0008 | 0.0009 |

Test Filter Type :

Test 1: Penetration (media calculated 30 sec after the test beginning)

Test 2: Max Penetration till 120 mg aerosol exposition

Test 3: Penetration (media calculated 30 sec after the test beginning) after 120 mg aerosol exposition and 24h storage

Marking R means that the filter is reusable for more than one workshift.





FILTER

Model: 203 A2B2E2K2HgP3 R D
P/N 124540000

“D” clogging test with Dolomite Dust.

Filter is submitted to an obstruction test with a concentration of Dolomite of 263 mg.h.m³.
Inhalation resistance: a 95 l/min: 8.4 mbar (request < 10.5 bar)

| Filter type | Testing Flow | Testing Aerosol | Penetration Max Allowed (%) | Penetration Max Measured (%) |
|-------------|--------------|-----------------|-----------------------------|------------------------------|
| P R | 95 | NaCl | 0.05 | 0.0008 |
| | | Paraffin oil | 0.05 | 0.0008 |

Marking D means the filter passed the clogging test with Dolomite dust and it has high performance in dusty and sandy settings.

Limitations for use

Do not use in areas where the oxygen concentration is lower than 17% in volume nor in presence of gases different from those clearly indicated. For type Hg P3 Filter the maximum use duration is 50 h.

CLASSIFICATION

Filter complying with Directive **89/686/EEC (PPE)**

Combined Filter, class 2 for gas protection and particle filter **class P3 R D**, to **EN 14387:2004 + A1:2008**.

Label colour code: brown, grey, yellow, green, white.

MARKING



MATERIALS

Housing: polypropylene

Filter Media: activated carbon and filter paper

STORAGE

Store at temperatures between -20 and +50°C and RH <80%

WEIGHT

312 g approximately.

DIMENSIONS/PACKING

The filter is sold in 4 piece boxes with dimensions 220 x 220 x 110 mm

SHELF LIFE

Filters duly stored and in their original packaging will last five years from production. The expiry date is stamped onto the filter label and its packaging.

For more information please check the notes along with the products or the ones published on the website: www.spasciani.com

NOTE: SPASCIANI SpA does not take any responsibility for any possible and unintentional mistake and reserve the faculty of modify materials and technical characteristics of its products at any time and without any notice. The pictures are purely indicative and may not represent the actual product described in the text.

