

CARTRIDGE

Model: 2030 A2

P/N 113900000

Gas filter with special snap-in connector for organic vapours having boiling point higher than 65°C. The cartridge shall be used in pairs with half masks **DUETTA** and **DUO** or full face masks type **TR 2002 CL2** and **TR 2002 CL3** with **DUPLA** adapter.



TECHNICAL DATA

Inhalation resistance

at 15 l/min: 0.8 mbar

at 47.5 l/min: 2.8 mbar

Duration at gases

Filter type	Class	Testing Gas	Testing Concentration (PPM)	Testing Flow (l/min)	Testing HR (%)	Breakthrough concentration (PPM)	Duration Required (min)	Duration Tested (min)
A	2	C ₆ H ₁₂	5000	15	70	10	35	45

Limitations for use

Do not use in areas where the oxygen concentration is lower than 17% in volume nor in presence of gases different from those clearly indicated, dusts, fumes and mists.

CLASSIFICATION

Filter complying with Directive **89/686/EEC (PPE)****Gas Cartridge / Filter, class 2, to EN 14387:2004 + A1:2008.**

Label colour code: brown

MARKING





CARTRIDGE

Model: 2030 A2
P/N 113900000

MATERIALS

Housing: polypropylene
Filter Media: activated carbon

STORAGE

Store at temperatures between -20 and +50°C and RH <80%

WEIGHT

95 g approximately

DIMENSIONS / PACKING

Cartridge is sold in 4 piece boxes with dimensions 175 x 115 x 90 mm

SHELF LIFE

Filters duly stored and in their original packaging will last five years from production. The expiry date is printed onto filter label and packaging.

For more information please check the notes along with the products or the ones published on the website: www.spasciani.com

NOTE: SPASCIANI SpA does not take any responsibility for any possible and unintentional mistake and reserve the faculty of modify materials and technical characteristics of its products at any time and without any notice. The pictures are purely indicative and may not represent the actual product described in the text.