



FILTER

Model: 202 A2P3

P/N 124420000

Combined filter with standard thread connector to **EN 148-1** for organic vapours having boiling point higher than 65°C, dusts, fumes, mists.

The filter can be used with full face masks type **TR 82**, **TR 2002 CL2** and **TR 2002 CL3**, halfmasks **ST 85** or equivalent, provided that they are fitted with EN 148-1 connector.



TECHNICAL DATA

Breathing resistance

at 30 l/min: 1.6 mbar

at 95 l/min: 5.2 mbar

Duration at gases

Filter type	Class	Test Gas	Test Concentration (PPM)	Test Flow (l/min)	Test HR (%)	Breakthrough concentration (PPM)	Duration Required (min)	Duration Tested (min)
A	2	C ₆ H ₁₂	5000	30	70	10	35	53

Particle filtration performance

Filter type	Class	Test flow	Aerosol (%)	Pen Max allowed (%)	Test 1 (%)	Test 2 (%)
P	3	95 l/min	NaCl	0.05	0.009	0.0003
			Paraffin oil	0.05	0.002	0.0012

Test 1: Maximum penetration till 120 mg aerosol exposition

Test 2: Penetration after 120 mg aerosol exposition and 24h storage



YOUR SAFETY MAKER

FILTER

Model: 202 A2P3

P/N 124420000



Limitations for use

Do not use in areas where the oxygen concentration is lower than 17% in volume nor in presence of gases different from those clearly indicated. The filter is reusable.

CLASSIFICATION

Filter complying with the provisions of Regulation (EU) **2016/425**, as III Category PPE.

Combined Filter, class 2 for gas protection and **class P3** for particle filter, according to **EN 14387:2021**.

Filter also conforms to EN 14387:2004+A1:2008 for the performance requirements.

Label colour code: brown, white.

MARKING

CE 0426

MATERIALS

Housing: polypropylene

Filter Media: activated carbon and filter paper

STORAGE

Store at temperatures between -20 and +50°C and R.H. <80%.

CHARACTERISTICS

Weight: 220 g (7.8 oz) approx.

Diameter max: 106 mm approx.

Height incl. thread: 85 mm approx.

Connection: standard thread EN 148-1:2018

PACKING

The filter is sold in 4 piece boxes with dimensions 220 x 220 x 105 mm.

SHELF LIFE

Filters duly stored and in their original packaging will last five years from production. The expiry date is stamped onto the filter label and its packaging.

For more information please check the notes along with the products or the ones published on the website www.spasciani.com

NOTA: SPASCIANI SpA does not take any responsibility for any possible and unintentional mistake and reserve the faculty of modify materials and technical characteristics of its products at any time and without any notice. The pictures are purely indicative and may not represent the actual product described in the text.